



Supported Protocols and Drivers

- PCIe 2.0, PCIe 3.0
- SATA 3/6 Gbps
- SAS 3/6/12 Gbps
- AHCI, NVMe

Supported Form Factors

- Edge Card
 - FHFL, FHHL, HHFL, HHHL
- 1.8", 2.5"
- U.2 / SFF
- mSATA
- M.2

System Scalability

- SX4e +
 - Engineering Lab Chassis
 - Up to 32 Parallel DUTs
- SX4-t / SX4a-t
 - Table-top Production Chassis
 - Up to 64 Parallel DUTs
- SX4-4t1z
 - 1-zone Production Chamber
 - Up to 256 Parallel DUTs
- SX4-8t2z
 - 2-zone Production Chamber
 - Up to 512 Parallel DUTs
- SX4-16t4z
 - 4-zone Production Chamber
 - Up to 1024 Parallel DUTs

Neosem Technology Inc

www.Neosemtech.com
sales@neosemtech.com

(512) 257-5000
11001 Lakeline Blvd.
Building 1, Suite 150
Austin, TX 78717

SX4-t SSD Test System



Complete PCIe , SAS , SATA SSD Test Coverage

The **SX4-t** is Neosem's 4th generation SSD test system. Designed for SSD test from the ground up, the SX4e-t is optimized to meet the rapidly evolving test requirements in the SSD market space. The unique architecture of the SX4e-t provides the flexibility to test all current SSD protocols – and – easily adapts to support new protocols as they emerge. In addition to complete protocol testing, the SX4e also fully supports Out-of-Band signal (DevSlp,WAKE,CLKREQ...) requirements and serial communications standards, such as for SMBus, UART, and others. The SX4-t+ also supports running Oakgate Technology's Storage Verification Framework (SVF) suite.

Maximum Scalability

Neosem engineered the SX4-t for maximum scalability. The architecture's basic components (Core Processor Boards, Protocol Boards, and DUT Power Boards) are repeated to offer the broadest range of parallelism. System layout and infrastructure assures distributed processing, no bandwidth loss, and no signal fidelity loss when scaling from the smallest engineering station to the largest HVM environmental chamber. The SX4-t economically scales from DUT counts as low as 4 DUTs to counts as high as 1024 DUTs.



www.SSDTester.com

Optimized Test Floor Operations

The integrated Test Board (TB) and Tray System from Neosem Technology is a revolutionary transport and test carrier solution specifically designed for SSD. Test Boards are hybrid assemblies of Signal and Power interface boards that are integrated into a durable framework, and can be designed to accommodate any DUT form factor. An EEPROM build on the Test Board stores the test results and can be output to a database. TB assemblies are compatible with all Neosem production systems, and they serve to transport as many as 64 DUTs – and their test results – between test stations



Customized Integration Solutions

Neosem Technology offers both proven, standardized solutions as well as custom integrated solutions. Neosem has worked with many of the Industry's handler companies to integrate Neosem hardware. Production chambers with integrated temperature control are combined with SX4-t electronics to allow parallel testing of as many as 1024 DUTs at -40 to 85C. Neosem Technology environmental chamber configurations range from one to four independently controlled zones.



SX4 Specifications

Minimum Configuration	4 to 64 DUTs
Maximum Configuration	Up to 1024 DUTs
PMU	MV, FVMI, FIMV on OOB Pins
Operating System	Operator Interface Windows 7 Test Execution : Linux
Test Application Development	C++ and Corresponding Test Recipe
Input Power	120-240V AC – 50 to 60HZ
Operating Temperature Range	18 to 28C – Air cooled
SSD Test Software	Neosem H3/H4 GUI or Optional OakGate SVF Suite

NEOSEM

Supported Protocols and Drivers

- PCIe 2.0, PCIe 3.0
- SATA 3/6 Gbps
- SAS 3/6/12 Gbps
- AHCI, NVMe

Supported Form Factors

- Edge Card
FHFL, FHHL, HHFL, HHHL
- 1.8", 2.5"
- U.2 / SFF
- mSATA
- M.2

System Scalability

- SX4e +
Engineering Lab Chassis
Up to 32 Parallel DUTs
- SX4-t / SX4a-t
Table-top Production Chassis
Up to 64 Parallel DUTs
- SX4-4t1z
1-zone Production Chamber
Up to 256 Parallel DUTs
- SX4-8t2z
2-zone Production Chamber
Up to 512 Parallel DUTs
- SX4-16t4z
4-zone Production Chamber
Up to 1024 Parallel DUTs

Neosem Technology Inc

www.Neosemtech.com
sales@neosemtech.com

(512) 257-5000
11001 Lake-line Blvd.
Building 1, Suite 150
Austin, TX 78717